water





M1400/M1500/M2100 Portable, Oil-Fired Models

M1000/M1200 Portable, Oil-Fired Models







M2000/M2200/M2300 Portable, Oil-Fired Models W/Hose Reel Kit Option

M1000/M1300/M1500 M2000/M2100/M2200 M2300/M3000/M3500 Stationary, Gas-Heated Models

Other A DF available Styles & Models Contact ADF for more information



HOT WATER HEATER Available in Oil or **Gas-Fired Models**



ALL ELECTRIC HEATED **Available in Models** Ranging up to 4GPM@3000PSI 230V/460V/3PH only



M2100/M2000 /M3000/M3500 Stationary, Gas Engine, Oil-Fired







M2100/M2000 M3000/M3500 Portable, Gas Engine, **Oil-Fired**


M2100/M2000 Portable, Gas Engine, **Oil-Fired**

				ME	DEL						
GENERAL SPECIFICATIONS	1000	1200	1300	1400	1500	2000	2100	2200	2300	3000	3500
Available Capacity's	2.1 gpm / 3gpm	3 gpm	4gpm	2.2 gpm / 3 gpm	3 gpm	4 gpm	3.5 gpm	3.6 gpm	4.2 gpm	4.0 gpm	5 gpm
Available Pressures	1000 / 700	1000	1200	1250 / 1000	1500	2000	2100	2500	1800	3000	3000
Pump Type	All pumps are Positive Displacement with ceramic plungers and oil bath crankcase										
Pump Motor	1-1/2 HP	2 HP	3 HP	2 HP	3 HP	5 HP	5 HP	6 HP	6 HP	7-1/2 HP	10 HP
Coil	1/2" ID A53 Sch 80 Pipe Vertically Fired										
Oil Fired Burner Models	U/L Approved, Oil Fired, Forced Air Burner w/ Automatic Ignition, 1/8 HP Burner Motor w/ thermal overload protection and a High Capacity oil/water separator Fuel Filter										
Gas Fired Burner Models		Rin	g Type Aspirating	Jet Gas Fired Burner	w/ Natural Dr	aft - All controls At	GA approved - Avai	lable in Natural G	as or L.P. Gas		
Temperature Control	Adjustable to 210 degs. F										
Flow Switch	Automatically shuts down burner when water flow has stopped										
Unloader Valve	Provides pressure relief for pump when trigger gun is closed										
Trigger Gun	Trigger shut off with insulated handle										
Wand	35" (88.9 CM) with insulated grip, extra extensions optional										
Hose			3/8 (9.5 MI	M) x 50 ft. (15.25 M) wi	re braided; 12	000 PSI (843.6 KI	G/CM) burst rating,	extra lengths opti	onali		
Nozzle	Sprayflex nozzle adjustment 0 through 80 degs.										
Float Tank	304 Stainless Steel										
Portability	Oil Fired Models Standard on (4) pneumatic wheels - Gas Fired Models Stationary										




ADF has a large selection of highly concentrated, biodegradable detergents.






- choose from, with pressures ranging from 1000 to 4000 PSI.
- Available in electric motor and gasoline driven models.
- Industrial grade pumps and motors.
- · Trigger shut-off gun on all models.





available in standard sizes ranging from 24" x 30" to 36" x 96" **CUSTOM SIZES AVAILABLE**



We also manufacture a full line of

to meet virtually every cleaning application.





